

普通应用产品- IEPE三轴型



型号	3263A2	3313A3	65	356A02
性能描述	IEPE型，三轴加速度传感器	IEPE型，三轴加速度传感器	IEPE型，通用型三轴加速度传感器	IEPE型，三轴加速度传感器
量程 g	± 50	± 500	± 500/± 50	± 500
灵敏度mV/g	100	10	10/100	10
响应频率Hz	0.3-10000	1.2-10000	0.4-10000	1-5000
传感器类型	IEPE	IEPE	IEPE	IEPE
电气接口	4PIN	4PIN	4PIN	1/4-28 4PIN
安装接口	4-40	1/4-28	螺柱	10-32螺纹
重量g	5.6	4	5	10.5
体积mm	12×12×11	11.9×9.1×9.1	10×10×10	14×20.3×14
工作温度 °C	-51...121	-51...121	-55...125	-54...163
其他	3263A1: ± 500g 3263A3: ± 100g 3263A8T: ± 50g	3313A2: ± 1000g 3313A1: ± 5000g		356A15: ± 50g 356A16: ± 50g 356A17: ± 10g



型号	356B18	356A16	354C02	340A50
性能描述	IEPE型，三轴加速度传感器	IEPE型，三轴加速度传感器	IEPE型，三轴加速度传感器	电荷型，三轴加速度传感器
量程 g	± 5	± 50	± 500	± 1000
灵敏度mV/g	1000	100	10	2.7
响应频率Hz	0.5-3000	0.5-4500	0.5-2000	8000
传感器类型	IEPE	IEPE	IEPE	PE
电气接口	1/4-28	1/4-28	1/4-28	M3
安装接口	10-32	10-32	通孔	通孔
重量g	25	7.4	15.5	11.0
体积mm	20.3×20.3×20.3	14×14×14	13/16in×11.4	10.2×21.6×12.7
工作温度 °C	-29...77	-54...80	-54...121	-70...260
其他		356A17:10g	354C03:50g	